



## Product Overview

IgniteNet™'s MetroLinq™ 2.5 - 60 is the world's first cost-effective high capacity 60GHz PTP radio enabling high performance, interference-free connections worldwide. The MetroLinq™ 2.5 - 60 has an added advantage of being license-free in most markets globally, allowing ultra fast deployment and without the hassle of other frequency bands requiring a license. The MetroLinq™ also includes a second 5GHz radio which can be configured as PtP (backup) to provide integrated redundancy without and additional hardware or complexity.

## Key Features and Benefits

### Interference-Free & Unlicensed Band

The IgniteNet™ MetroLinq™ 2.5 - 60 offers unprecedented performance - combining both the benefits of unlicensed band operation with no interference!

### Dual Band 60GHz & 5GHz Operation

The MetroLinq™ 2.5 - 60 includes a second 5GHz radio which can be configured as a backup to the 60GHz to provide automatic failover during adverse conditions. This allows links to be extended further without effecting link availability

### Powerful, Flexible Configuration

The MetroLinq™ Base Station can operate either as a stand-alone device or as a coordinated, cloud-managed device, easily meeting the requirements of any installation.

### Robust Weather-Resistant Design

The MetroLinq™ Base Station features a hybrid metal/plastic design built to withstand the harshest environments including precipitation, hot/cold weather and high/low humidities.

## Product Variants



35cm Size w/ 60GHz + 5GHz



19cm Size w/ 60GHz + 5GHz



# MetroLinq™ 2.5 60

Cloud-Enabled Outdoor 60GHz PTP + 5GHz

## Features

### HARDWARE FEATURES

- ✓ 1x 2.5 Gigabit Ethernet Port (PoE IN 24-48v)
- ✓ 1x SFP Port
- ✓ 1x Screw Terminal Block (DC Power IN 24-48v)
- ✓ 1x USB 3.0 Port
- ✓ Dual flash image support

### LEDs

- ✓ Power, Ethernet, Wireless, Health/Status

### DIMENSIONS (L x W x H)

- ✓ 350 x 350 x 200 mm (ML-60-35)
- ✓ 190 x 190 x 120 mm (ML-60-19)

### WEIGHT

- ✓ TBD

### POWER

- ✓ 24-48V/1.5A passive Gigabit PoE or DC

### OPERATING ENVIRONMENT

- ✓ Operating Temperature: -40C° to +70C°
- ✓ Store Temperature: -40C° to 70C°
- ✓ Operating Humidity: 10 to 90% non-condensing (RH)

### REGULATORY / STANDARDS COMPLIANCE

- ✓ FCC/IC
- ✓ CE

### RF PERFORMANCE (TX)

- ✓ 60GHz:  
14dBm @ 2.5Gbps
- ✓ 5GHz:  
27dBm @ 6Mbps, 23dBm @ 866 Mbps

### RF PERFORMANCE (RX)

- ✓ 60GHz:  
-74dBm @MCS1; -60dBm @ MCS9
- ✓ 5GHz:  
-94dBm @MCS0; -72dBm @ MCS15

### KEY FEATURES

- ✓ 2.5+ Gbps Aggregate throughput; dynamically allocated (60GHz)
- ✓ Management VLAN support and VLAN pass-through
- ✓ Supports Service Provider and Enterprise type networks
- ✓ Stand-alone or Cloud-controlled operating modes
- ✓ Link failover/backup (60GHz + 5GHz) Per Client
- ✓ 128bit AES Encryption (standard; 5GHz, and 60GHz)
- ✓ SNMP Monitoring with Private MIB

### APPLICATIONS

- ✓ Fixed Wireless Access (broadband)
- ✓ 3G/4G Backhaul
- ✓ Metro WiFi
- ✓ Campus Interconnection
- ✓ Hybrid Fiber/Wireless Networks

## Ordering Information

Part Number	Description
ML2.5-60-35-XX	60GHz Outdoor + 5GHz w/ Int 42dBi (60GHz) & 22dBi (5GHz) antenna, 2500Mbps + SFP
ML2.5-60-35-1-XX	60GHz Outdoor + 5GHz w/ Int 42dBi (60GHz) & External 5Ghz, 2500Mbps + SFP
ML2.5-60-19-XX	60GHz Outdoor + 5GHz w/ Int 36dBi (60GHz) & 16dBi (5GHz) antenna, 2500Mbps + SFP
ML2.5-60-19-1-XX	60GHz Outdoor + 5GHz w/ Int 36dBi (60GHz) & External 5GHz, 2500Mbps + SFP

**\*\*XX is used to denote localization (US, EU, UK, CN)**

## Contact



### Worldwide

20 Mason  
Irvine, CA 92618  
USA  
[sales@ignitenet.com](mailto:sales@ignitenet.com)

### Asia

No. 1 Creation Road III,  
Hsinchu Science Park,  
30077, Taiwan, R.O.C.  
[sales@ignitenet.com](mailto:sales@ignitenet.com)

**Fire Up Your Network™ ...**

Enterprise Wireless | Broadband Wireless | Fiber

[www.ignitenet.com](http://www.ignitenet.com)