

# **AC1300** Dual Antennas High-Gain Wireless USB Adapter

**Boost Wireless Range** 













# Highlights

### High-Speed, Dual Band WiFi

The Archer T4U Plus grants your PC access to 802.11ac technology while receiving WiFi signals on two separate bands, boosting speeds up to 1300 Mbps (up to 400 Mbps on 2.4 GHz and 867 Mbps on 5 GHz). This means better networking experience for all your online needs. Choose the 2.4 GHz band for web browsing,email, and social media,or switch to 5 GHz for gaming,HD streaming, and large file downloads.



### Dual High-Gain Antennas, Broader Coverage

Two powerful high-gain external antennas ensure stronger signal transmission and reception between web devices and your router even from farther away or across multiple walls and floors. Enjoy stable wireless connections and faster speeds without WiFi drops and lag.





# Highlights

### Flexible Design for Easy Use

#### Rotate and adjust the antenna 180° for the best reception in different environments. The adapter's desktop-style design and 1.0m USB cable help you find the best spot for network reception.Enjoy an easy and desktop- friendly setup for flexible deployment.

### A Great Match for Faster Speeds

Connect the newest hardware with USB 3.0. USB 3.0 is specially suited for the 802.11ac Wi-Fi protocal and utilizes its transfer rate for better connections. Take full advantage of USB3.0 and 802.11ac Wi-Fi for optimized network performance.







# **Specifications**

### WLAN Features

• Wireless Standards: IEEE 802.11b/g/n 2.4 GHz, IEEE 802.11a/n/ac 5 GHz	11n HT20: -70
· Signal Rate:	11g 54Mbps:
5 GHz:	11b 11Mbps:
11ac: Up to 867 Mbps(dynamic)	· Transmit Powe
11n: Up to 400 Mbps(dynamic)	5 GHz: 20dBm
11a: Up to 54 Mbps(dynamic)	2.4 GHz : 19dB
2.4 GHz:	· Wireless Mode
11n: Up to 400 Mbps(dynamic)	· Interface: USB
11g: Up to 54 Mbps(dynamic)	· Wireless Secu
11b: Up to 11 Mbps(dynamic)	
· Reception Sensitivity:	
5 GHz:	
11ac VHT80: -60dBm	
11ac VHT40: -64dBm	
11ac VHT20: -69dBm	
11n HT40: -71dBm	
11n HT20: -74dBm	
11a 54Mbps: -76dBm	
2.4 GHz:	
11n HT40: -68dBm	

70dBm

s: -74dBm

s: -86dBm

wer:

Bm(FCC) / 18dBm(CE) (EIRP)

dBm(FCC) / 17dBm(CE) (EIRP)

odes: Infrastructure mode

SB 3.0

curity: WPA/WPA2/WPA3 encryption standards

# **Specifications**

### Hardware

- · Antennas: 2× External High Gain Antennas
- · LED: Status
- Dimensions:  $84 \times 156.3 \times 19.2 \text{ mm} (3.3 \times 6.2 \times 0.76 \text{ in})$

### Others

- · Package Contents Quick Installation Guide Resource CD 1-meter USB 3.0 Cable
- · Certification FCC, CE, RoHS
- System Requirements
- Environment Storage Humidity: 5%~90% non-condensing



📴 🔚 For more information, please visit https://www.tp-link.com/en/home-networking/high-gain-adapter/archer-t4u-plus/

or scan the QR code left

Attention: This device may only be used indoors in all EU member states and EFTA countries.

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Corporation Limited. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright ©2023 TP-Link Technologies Co., Ltd. All rights reserved. <sup>†</sup>Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and wireless coverage, and number of connected devices are not guaranteed and will vary as a result of network conditions, AP limitations, and environmental factors, including

building materials, obstacles, volume and density of traffic, and AP location.

AC1300 Dual Antennas High-Gain Wireless USB Adapter Archer T4U Plus

Supported operating systems include Windows 11/10/8.1/8/7,

Operating Temperature: 0°C~40°C (32°F ~104°F) Operating Humidity: 10%~90% non-condensing